



Introducing the O2 Mini series of LED track fixtures:  
High performance output in a sleek, compact design



**O2** MINI


high performance  
LED track fixtures

## Introducing the O2 Mini series of LED track fixtures: High performance output in a sleek, compact design


- Available in both a vertical and horizontal configuration, the die-cast aluminum housings feature a clean, modern aesthetic designed to quietly compliment any retail or commercial environment
- Three wattage/lumen packages are available to provide the right amount of light for your application: 11W (950lm), 16W (1200lm) and 24W (1500lm)
- Spot (13°), Medium (27°), and Flood (40°) beam distributions are achieved utilizing custom engineered TIR optics specifically designed for use with a multi-chip LED array, resulting in a uniform beam that maximizes output and minimizes glare
- Four (4) standard color temperatures (2700K, 3000K, 3500K, 4000K) are available in both standard (83) and high (93+) CRI, all feature excellent color consistency within a 2-Step MacAdam Ellipse tolerance
- Utilizing the Snoot/Accessory Holder, the O2 Mini will accommodate up to two (2) lenses or honeycomb louvers
- Designed and rated for 50,000 hours of life, backed by a five (5) year replacement guarantee



### Vertical Housing



### Horizontal Housing



FIXTURE	ORIENTATION	BEAM	COLOR TEMP		DIMMING	FINISH
CTL8061 - 11W	H - Horizontal	S - Spot	27	2700K, 83 CRI	D - Dimming	B - Black
CTL8062 - 16W	V - Vertical	M - Medium	3	3000K, 83 CRI		P - White
CTL8063 - 24W		F - Flood	35	3500K, 83 CRI		S - Silver
			4	4000K, 83 CRI		
			27C	2700K, 93+ CRI		
			3C	3000K, 93+ CRI		
			35C	3500K, 93+ CRI		
			4C	4000K, 90+ CRI		

### ACCESSORIES

FA-43-(B,P,S) - 1" Snoot/Accessory Holder  
 FA-16 60MM - Black Honeycomb Louver  
 LF16-(A, B, CL, G, LB, R, RO, Y, 73, LS, SL, UV) 60MM  
 3-3/4" Dia. Glass Lenses

#### Color/Pattern Legend

-A (Amber), -B (Blue), -CL (Clear), -G (Green), -LB (Light Blue), -R (Red), -RO (Rose), -Y (Yellow), -73 (Spread Lens), -LS (Linear Spread Lens), -SL (Soft Light), -UV (Optivex UV Filter)