

DATE PROJECT TYPE

CTL2830 SERIES | PAR30 Front Relamping Gimbal Line Voltage Track Luminaire



MAX. WATTAGE	One (1) 120V 75W PAR30, E26 Medium Base	
COMPATIBILITY	CTL Units are compatible with ConTech Lighting LT/LT2 Single Circuit/Two Circuit Track Systems as well as Juno ^{®1} Lighting Trac-Lites [™] (R) and Trac-Master [™] (T, TU) Track Systems	
	HTL Units are compatible with Halo ² Power-Trac (L64, L65) and Lazer (LZR) Track Systems	
	LTL Units are compatible with Lightolier ³ Lytespan [®] 6000/1/2 Track Systems	
LISTINGS	cCSAus Certified Suitable for Dry Locations only	
WARRANTY	One (1) year replacement after date of purchase	

PRODUCT DETAILS

- Two-plane Gimbal design for excellent aiming; 360° horizontal swivel and 150° adjustability in the vertical plane
- Sure-Set Yoke holds the luminaire firmly in place

Select SKUs Shipped within 48-Hours

- Integral ON/OFF switch and track polarity indicator are standard
- Will accept one (1) LF30 lens or LA-38 Egg Crate Louver by using the FA-28 Black Accessory Mounting Clips
- Standard ConTech track luminaires (CTL Units) are cCSAus certified as-is for use with ConTech Lighting LT/LT2 Single Circuit/Two Circuit and Luxbeam Track Systems, as well as Juno® Lighting Trac-Master™ Systems.
- By changing the prefix of the part number, ConTech can install inserts which make our fixtures compatible with other manufacturers. Replace "CTL" with "HTL" for Halo® Power-Trac and Lazer-Track systems, and "LTL" for Lightolier Lytespan™ systems. For more information, consult factory.
- All luminaire models are eligible for **Speed**Ship
 - 1. Juno is a registered trademark of Juno Lighting
 - 2. Halo is a registered trademark of Cooper Lighting
 - 3. Lightolier is a registered trademark of Signify

ORDERING INFORMATION

Example Order: CTL2830 - P

		—
Track System	Luminaire	Finish
CTL - ConTech	2830	B - Black
HTL - Halo		P - White
ITI - Lightolier		

: These Model Options are eligible for **Speed**Ship

Accessories

FA-28 - Black Accessory Mounting Clips

LF30-* - 4-11/16-Inch Dia. Tempered Glass Lenses

LA-38-(B,P) - 4-3/4-Inch Dia. Egg Crate Louver

*Color/Pattern Legend

-73 (Spread Lens), -LS (Linear Spread Lens), -SL (Soft Light), -SOL (Solite), -UV (Optivex UV Filter), -A (Amber), -B (Blue), -CL (Clear), -G (Green), -LB (Light Blue), -R (Red), -RO (Rose), -Y (Yellow)