

# LVR316R-SA

# StopAire Low Voltage Recessed Remodel Downlight; Housing Only

Catalog	No.
0 01 001 00	

Project \_

### **Specifications/Features**

### Housing/Mounting

Low silhouette design for remodeling applications in solid or suspended ceilings.

Narrow fixture design for fast installation through ceiling opening minimizes remodeling mess.

Retractable mounting clips allow easy installation into existing ceiling. Fixture is easily installed through ceiling opening.

Retractable mounting clips lock fixture in place and adjust for different ceiling thicknesses from 1/2" to 1".

## Lamp/Electrical

(1) 10W Max. or (1) 50W Max., 12V MR16, GU5.3 base.

Class H "in-line" magnetic transformer is prewired and thermally protected. 120V in/12V out. Conveniently mounted to end of J-Box and is replaceable to simplify future maintenance.

(6) 1/2" knock outs and spring latch access plates in J-box.

Lamp housing is removeable through ceiling aperture for access to J-Box. Can be used with low voltage, magnetic dimming controls for optimal control of illumination.

Ceramic terminal block socket.

#### **Trims**

Baffle, multiplier, wall wash, accent and adjustable trim options available to suit a broad range of applications. See "Trims for 3" Low Voltage Recessed Housings" spec sheet for details.

This fixture is covered by ConTech's full one (1) year replacement guarantee after date of purchase.


### Labels/Usage

cCSAus Certified. Suitable for damp locations.

Conforms to Washington State Energy Code (WSEC) for low air filtration.

Tested in accordance with ASTM E283 (2.0 CFM or less).





### **Ordering Information**

Example Order:	LVR316R-SA IOM	CTR3I2-P		
	Housing/Voltage		Trims	

LVR316R-SA 10M - 120V/12V/10W LVR316R-SA - 120V/12V/50W

www.contechlighting.com

For Trims, see "Trims for 3" Low Voltage Recessed Housings" spec sheet.



Catalog No	

_			
Tyne			
1 ANG			

# Trims for 3" Low Voltage Recessed Housings


Proiect \_

4-1/4"

0.D.

1-3/8" Aperture

- All CTR3 Series Trims are cCSAus Certified and Suitable for Damp Locations; only Shower Trims are Wet Location Listed
- All Trims have White Trim finish unless specified
- For Trims designed for use with MR16 Lamps, ConTech Lighting provides a clear, Tempered Safety Glass Lens that should only be
- used with open MR16 Lamps; not with MR16 Lamps that contain an integral Glass Lens
- If use of MR16 with Front Glass is required, remove the factory provided Safety Lens; Lens should also be removed when using MR16 LED Lamps
- Consult factory for LED Lamp compatibility




### CTR301 Series

Adjustable Baffle

15° Vertical swing, 45mm lens. Trim can hold up to two (2) lenses with stepped lens holder (included). Insert 45mm lens on lower level of lamp seat, instert 50mm lens onto higher level.

CTR301-WHT - Adjustable White Baffle



### CTR303N Series

Slotted Wall Wash

Internal 50° swing adjustment (25° from Nadir), external 358° rotation. Slot aperture permits maximum beam area adjustment for either wall wash or concealed accent lighting effects. Black interior surface.

CTR303N-P - White Slotted Wall Wash



### CTR307 Series

Adjustable Pin Spot

Deep baffle for maximum lamp concealment. May be used as a pin spot style downlight or an adjustable accent light. 35° Vertical adjustment. 45mm Lens. Trim can hold up to two (2) lenses with stepped lens holder (included). Insert 45mm lens on lower level of lamp seat, instert 50mm lens onto higher level.

CTR307-B - Black Baffle, Black Trim



### CTR302 Series

Adjustable Multiplier

37° Vertical adjustment, 45mm lens. Trim can hold up to two (2) lenses with stepped lens holder (included). Insert 45mm lens on lower level of lamp seat, instert 50mm lens onto higher level.

CTR302-B-BLKN - Black Reflector, Black Trim CTR302-P-CLR - Clear Reflector, White Trim


CTR302-P-BLK - Black Reflector, White Trim CTR302-P-WHT - White Reflector, White Trim

CTR302STCLR - Clear Reflector, **Brushed Stainless Steel Trim**  CTR305 Series

Pin Spot

Downlight Only, 50mm Lens. Trim can hold up to two (2) lenses with stepped lens holder (included), Insert 45mm lens on lower level of lamp seat, instert 50mm lens onto higher level.

CTR305-CLR - Clear Cut-Off Reflector, White Trim




### CTR325 Series

Fully Adjustable

Die cast, fully adjustable, round lampholder and backplate. Easy relamping with twist-off front retaining ring. Unsurpassed aiming flexibility: 87° vertical, 359° rotational. 50mm lens.

CTR325-B - Black CTR325-P - White



### CTR312

Flat Glass

Etched Glass for light diffusion.

CTR312-P - Flat Glass, White Trim

### CTR311FR

www.contechlighting.com

Frosted Flat Glass Shower Light Shower light trim, double neoprene gasketed. cULus Listed for wet location.

CTR311FR-P - Frosted Flat Glass Shower Light, White Trim



Fully Adjustable

Unsurpassed aiming flexibility: 87° vertical, 359° rotational. Front access, spring latch lamp retainer ring, black finish (optional white retainer rign available: 1623/24 WHITE, ordered separately). Exclusive stainless flat springs insure firm, close-to-ceiling mounting. Accepts only one 47mm lens; if louver is required (FA-16 45MM), remove safety lens and use front glass MR16 lamp.

CTR324-P - White