



NTEK/NHTEK

2-Circuit/2-Neutral Track Installation Accessories 120V and 277V Series




Live End Feeds




NTEK11-(B,P,S) 120V **NHTEK11-(B,P,S)** 277V Live End Feed

NTEK12-(B,P,S) 120V NHTEK12-(B,P,S) 277V Live End Feed, Reverse Polarity




Live Middle Feed

NTEK14-(B,P,S) 120V NHTEK14-(B,P,S) 277V



Feedable L-Connector


NTEK34-(B,P,S) 120V NHTEK34-(B,P,S) 277V Adjustable Polarity



Feedable T-Connectors


NTEK39-(B,P,S) 120V NHTEK39-(B,P,S) 277V Feedable T-Connector, Adj. Right Polarity

NTEK40-(B,P,S) 120V NHTEK40-(B,P,S) 277V Feedable T-Connector, Adj. Left Polarity



Feedable X-Connector

NTEK38-(B,P,S) 120V NHTEK38-(B,P,S) 277V



Adjustable Connector

NTEK24-(B,P,S) 120V **NHTEK24-(B,P,S)** 277V Catalog No.

Type _____

Project _____



Linear Coupler

NTEK21-(B,P,S) 120V NHTEK21-(B,P,S) 277V

Does not add length to track run



Dead Ends

NTEK41-(B,P,S) 120V NHTEK41-(B,P,S) 277V



Recessed End Cap


NFTP41-U

For safe, flush mounting applications. Natural galvanized steel.



Outlet Box Cover

NGES15-(B,P,S)



120V Fixture Adapter

NTEK70-(B,P,S)

Switchable between circuits and on/off. Consult factory for 277V.



Track Length and Field Cutting Tool

NXTSV12

All-in-one hand tool, bends conductors to manufacturer specifications and includes gauge to verify correcdt length.



Stem Kits

MCDIIC12 /D D\ 12" Ctom

 NSPUS12-(B,P)
 12" Stem

 NSPUS18-(B,P)
 18" Stem

 NSPUS24-(B,P)
 24" Stem


 NSPUS48-(B,P)
 48" Stem

 Includes stem and canopy.



NTEK/NHTEK

2-Circuit/2-Neutral Track Installation Accessories 120V and 277V Series



Ceiling Mount Accessories

NSKB30-(B,P,S) Ceiling Cup For threaded rod or cable mount (rod/cable not included).

NSKB31 Threaded Rod 1/4" Dia., 6' Length. UNLook Finish.

NSKB34 5' Cable NSKB34/3M 9' Cable Custom lengths as special of

Custom lengths as special order. UNLook Finish.

NSKB12-(B,P,S) Mounting ClipFor threaded rod or cable mount (rod/cable not included).



Mounting Clips



NSKBX12-(B,P,S) Deep Tile Mounting Clips

NSKBT12-(B,P,S) Mounting Clips for T-Bar Ceilings



Stem Suspension Points

NSP4P-(B,P,S) Universal Suspension Point

Includes bracket and cover, stem not included. Also works with cable and threaded rod suspension.


Catalog No		

Type _____


Project _____

Track Dimensions and Configurations

NTEK and NHTEK track are polarized and manufactured with indentifying ridges (dotted line on diagrams). Refer to these diagrams to ensure proper connector selection.



*Actual dimensions or field cut to length



Actual 48", 96" or 144" length or field cut to length

Actual 48", 96" or 144" length or field cut to length

Add 3.25" for Live End Feed (1)

Actual 48", 96" or 144" length or Field Cut to length

Actual 48", 96" or 144" length or Field Cut to length

No dimension added with Linear Coupler (2)

Actual 48", 96" or 144" length or Field Cut to length

Actual 48", 96" or 144" length or Field Cut to length

KEY:

- 1 NTEK11 Live End Feed NTEK12 Live End Feed Reverse Polarity
- 2 NTEK21 Linear Coupler

Add 3.25" for Live End Feed (1)

- 3 NTEK14 Live Middle Feed4 NTEK34 Feedable L-Connector Adj. Polarity
- **5a NTEK39** Feedable T-Connector Adj. Polarity

Add 5" for Live Middle Feed (3)

- **5b NTEK40** Feedable T-Connector Adj. Left Polarity
- 6 NTEK38 Feedable X-Connector