

DATE PROJECT TYPE

# PERFORMANCE LED TAPELIGHT | 24V Tunable White (TW) Connectors

## Hardwire Power Connectors



**TLCIP12HWTW**  
 24V Tunable White Male Power Connector  
 Includes wire pigtail end and one (1) male flex tape connector. Use with TW Controller and LED Power Repeater.  
 Use with 24V Tunable White (TW) Performance LED Tapelight only



**TLCOP12HWTW**  
 24V Tunable White Female Power Connector  
 Includes wire pigtail end and one (1) female flex tape connector. Use with TW Controller and LED Power Repeater.  
 Use with 24V Tunable White (TW) Performance LED Tapelight only

**TLCIP12HWTW** - 12 IN Tunable White Hardwire Male Power Connector **Quantity**

**TLCOP12HWTW** - 12 IN Tunable White Hardwire Female Power Connector **Quantity**

## Linear Connectors



**TLCM \* RGB Series**  
 Bridge Connector  
 Blank section used to bridge gaps where LEDs are not necessary.  
 Use with RGB and Tunable White (TW) Performance LED Tapelight only



**TLCXRGB**  
 Cross Connector  
 Used to connect up to four (4) tapelight segments. May be cut to create 2-way "L" connection or 3-way "T" connection.  
 Use with RGB and Tunable White (TW) Performance LED Tapelight only

**TLCM2RGB** - 2 IN **TLCM6BRGB** - 6 IN **Quantity**  
**TLCM12RG** - 12 IN

**TLCXRGB** - RGB and Tunable White Cross Connector **Quantity**



**TLCFFRGB**  
 Short Female-to-Female Connector  
 Used to connect male tapelight ends (when tapelight is cut two male ends remain).  
 Use with RGB and Tunable White (TW) Performance LED Tapelight only

**TLCFFRGB** - RGB and Tunable White Short Female-to-Female Connector **Quantity**