

DATE

PROJECT

TYPE

PERFORMANCE LED TAPELIGHT | RGB & RGBW TLT Series Controllers



TLP RGBWTC
RGB/RGBW Touch Controller
 Dial Touch Controller, select color by using color wheel. Speed and brightness control. Pre-selected modes. 20AMP Max.
 6-7/8" L x 1-3/4" W x 1-3/16" D
 Use with 12V or 24V RGB/RGBW Performance LED Tapelight



TLP RGBWRF
RGB/RGBW 28-Key Remote Controller
 8-Key RF Remote for color, speed, and brightness control. Seven (7) programmable scenes. 20AMP Max.
 6-7/8" L x 1-3/4" W x 1-3/16" D
 Use with 12V or 24V RGB/RGBW Performance LED Tapelight

TLP RGBWTC - RGB/RGBW Touch Controller

Quantity

TLP RGBRF - 12V/24V Dimming Controller with RF Remote Control

Quantity



TLP INT
DMX 512 CV Decoder
 Designed to convert universal DMX 512 signal to PWM signal when used with a DMX 512 console (by others). Use with non-dimming tapelight power supplies.
 Not UL listed for outdoor use.
 6-3/16" L x 3-1/8" W x 1-5/8" D
 Use with 12V or 24V Performance LED Tapelight; can control white, single color or RGB LEDs



TLP RTW
4-Channel Power Repeater
 Enables synchronized control of multiple runs from one controller.
 5-5/16" L x 1-3/4" W x 1-1/8" D
 Use with 12V or 24V Static Color, TW, RGB or RGBW Performance LED Tapelight

TLP INT - 12V/24V DMX 512 CV Decoder

Quantity

TLP RTW - 12V/24V LED 4-Channel Power Repeater

Quantity